



Monark - service

Inställningsvä

Motor	ILO					
Typ	F 48	FP 50	G 50	FM 100	FM 120	MG 150 L
Slagvolym (cm ³)	48	48	49	98	118	146
Cylinderdiameter (mm)	37	38	38	50	55	57
Slaglängd (mm)	44	43	43	50	50	58
Effekt (hk)	0,8	0,8	0,8	2,8	4,0	9,0
Förgasare typ	Bing 1/9,5/3 1/9,5/40	Bing 1/9,5/41 1/9,5/44 1/9,5/47	Pallas G 8/131	Bing 1/16/2 1/16/31	Bing 1/16/3 1/16/43	Bing 1/22/3 1/22/7 1/22/7
Huvudmunstycke *	48	(60) 58 (58) 56 (60) 58	(50) 47	(80) 80 (80) 80	(80) 75 (80) 75	(95) 90 (125) 120 (125) 120
Tomgångsmunstycke	—	—	—	35 40	40 40	45 35 35
Nålmunstycke	2,10	2,10 2,10 2,10	Spridarmun- stycke 3205	2,60 2,60	2,60 2,60	2,68 1508 1508
Nålställning *	(2) 2	(3) 3 (2) 2 (3) 3	—	(2) 2 (2) 2	(2) 2 (2) 2	(3) 3 (3) 3 (3) 3
Luftregleringsskruv * Utskruvade varv	—	—	—	(2½) 2½ (2½) 2½	(2½) 2½ (2½) 2½	(1) 1 (1½) 1½ (1½) 1½
El-anläggning, typ	Siba MZ 2 R	Noris ELZ 6/17/1 L Noris ULZ 6/16,5 L Stefa C 2/75/02 Stefa C 2/75/04	Stefa C 2/75	Noris SLZ 6/7	Bosch ULA 1 CR 13	Bosch LM/UT 1/142/27 LM/UT 1/142/30
Spänning (volt)	Ljusanläggning saknas	6	6	6	6	6
Effekt (watt)	Ljusanläggning saknas	16,5	16,5	7,5	15	27 30
Brytavstånd (mm)	0,3–0,4	0,3–0,4	0,3–0,4	0,4–0,5	0,4–0,5	0,4–0,5
Förtändning (mm)	3	4,0–4,5	2,4–2,6	3,5–4,0	3,5–4,0	3,5–4,0
Abrissavstånd (mm)	Ej inställbart	9–12 7–10	7–10	7,5–10	7,5–10	7,5–10
Tändstift, typ	Bosch W 175 T 1 Lodge H 14 K. L. G. F 70	Bosch W 225 T 1 Lodge HNP K. L. G. F 80	Bosch W 225 T 1 Lodge HNP K. L. G. F 80	Bosch M 95 T 1 Lodge C 3 K. L. G. M 30	Bosch M 145 T 1 Lodge C 3 K. L. G. M 50	Bosch M 225 T 1 Lodge HIP K. L. G. M 80
Elektroavstånd (mm)	0,5	0,5	0,5	0,5	0,5	0,5
Olja för växellåda och koppling	—	—	SAE 80	Vinter: Mobil Grease Nr 1 Sommar: Mobil Grease Nr 2	Vinter: Mobil Grease Nr 1 Sommar: Mobil Grease Nr 2	SAE 30
Rymd (liter)	—	—	0,2	Växellåda 0,11 Koppling 0,16	Växellåda 0,11 Koppling 0,16	0,7

*) Värderna inom parentes avse inkrörning.

svärden för monarped- och motorcykelm

					BSA	CZ	
MG 150 L	MG 175 F	M 175	M 250	M 2-125	125 cc	125 cc, mod. B	125 cc, mod. C
146	173	173	247	244	123	123	123
57	58	58	65	52	52	52	52
58	66	66	75	58	58	58	58
9,0	8,2	8,2	11,4	15,1	4,0	4,5	4,5
1/22/38 g 1/22/70 1/22/71	Bing 1/20/8 1/22/38	Bing 1/20/8 1/24/31	Bing 1/26/14 1/27/1	Bing 1/24/71 1/24/81	Amal 261 361	Jikov 2916	Jikov 2918
(95) 90 (125) 120 (125) 120	(90) 85 (95) 90	(90) 85 (115) 110	(110) 105 (125) 120	(130) 125 (130) 125	(75) 70 (75) 70	(70) 65	(70) 65
45 35 35	45 45	45 50	55 35	35 35	—	—	—
2,68 1508 1508	2,68 2,68	2,68 2,68	2,68 1508	1508 1508	106 106	Standard	Standard
(3) 3 (3) 3 (3) 3	(3) 3 (3) 3	(3) 3 (2) 2	(3) 3 (3) 2	(3) 2 (3) 2	(3) 3 (3) 3	(3) 3	(3) 3
(1) 1 (1½) 1½ (1½) 1½	(1) 1 (1) 1	(1) 1 (1½) 1½	(1½) 1½ (1) 1-2	(1) 1 (1) 1	—	—	—
1/142/27R21 1/142/30R21	Noris MLZ 6/45/60S1	Noris MLZ Sn 6/45/60R	Noris MLZ Sna 45/60/1 R med automatisk tändförställning	Noris MLZ Sn 2/45/60 R MLZSn2/60/6-1500 1R	Wico	CZ	CZ
6	6	6	6	6	6	6	6
27 30	45-60	45-60	45-60	45-60	24 30	15	25
0,4-0,5	0,3-0,4	0,3-0,4	0,3-0,4	0,3-0,4	0,55	0,40-0,45	0,40-0,45
3,5-4,0	3,5-4,0	3,5-4,0	I viloläge 0,3-0,5	3,0-3,5	4,0	3,0-4,5	3,0-4,5
7,5-10	—	—	—	—	7-10	7-10	7-10
ch M 225 T 1 ge HIP G. M 80	Bosch W 225 T 1 Lodge HNP K. L. G. F 80	Bosch W 225 T 1 Lodge HNP K. L. G. F 80	14 mm 18 mm Bosch W240T1 M225T1 Lodge — HIP K.L.G. F 100 M 80	Bosch W 240 T 1 — K. L. G. F 100	Bosch W 145 T 1 Lodge C 14 K. L. G. F 50	Bosch W 145 T 1 Lodge C 14 K. L. G. F 50	Bosch W 175 T 1 Lodge H 14 K. L. G. F 70
0,5	0,7	0,7	0,7	0,7	0,5	0,5	0,5
SAE 30	SAE 30	SAE 30	SAE 30	SAE 30	SAE 30	SAE 30	SAE 30
0,7	0,7	1,25	1,1	1,4	0,45	0,5	0,55



CZ			JB			PILOT	
mod. B	125 cc, mod. C	150 cc, mod. C	48 cc	125 cc	150 cc	FM 50,1	FM 504
	123	148	48	128	148	49	49
	52	57	39	55	59	40,5	40
	58	58	40	54	54	38,25	39,5
	4,5	6,0	0,75	4,5	6,0	0,8	0,8
916	Jikov 2918	Jikov 2918	Amal 308	Amal 223 523	Amal 223 523 Bing 1/18/2	Pallas SF 8/90 F 8/9	Pallas F 8/9
65	(70) 65	(80) 75	(35) 32	(85) 80 (85) 80	(90) 85 (90) 85 (80) 75	(50) 47 (50) 47	(47) 47
	—	—	—	—	— 45	— —	—
ard	Standard	Standard	0745	107	107 2,68	Spridarmun- stycke 6308 6308	Spridarmun- stycke 6308
3	(3) 3	(3) 3	(2) 2	(3) 3	(3) 3 (3) 3	— —	—
	—	1½	—	—	—	—	—
	CZ	CZ	Stefa C 1/68 (25780) C 1/75-03	Stefa A 1/315 (20936)	Stefa A 3/315 (22660)	Stefa C 2/75-04 Stefa C 2/75-08 Stefa C 2/75-25 Stefa C 0/105-04	Stefa C 2/75-25
	6	6	6	6	6	6	6
	25	25	7	30	30	16,5	16,5
0,45	0,40—0,45	0,40—0,45	0,3—0,4	0,35—0,45	0,35—0,45	0,4—0,5	0,3—0,4
4,5	3,0—4,5	3,0—4,5	3,5—4,0	4,5	4,5	3,5	3,2—3,5
0	7—10	7—10	7—10	7—10	7—10	7—10	7—10
45 T1 0	Bosch W 175 T1 Lodge H 14 K. L. G. F 70	Bosch W 175 T1 Lodge H 14 K. L. G. F 70	Bosch W 145 T1 Lodge C 14 K. L. G. F 50	Bosch M 145 T1 Lodge C 3 K. L. G. M 50	Bosch M 145 T1 Lodge C 3 K. L. G. M 60	Bosch W 95 T1 — —	Bosch W 175 T1 Lodge H 14 K. L. G. F 70
	0,5	0,5	0,5	0,5	0,5	0,5	0,5
30	SAE 30	SAE 30	—	Mobil Grease Nr 2 som vid låga temp. uppblandas m. nå- got motorolja SAE 50	SAE 30	—	SAE 80
	0,55	0,55	—	0,2	0,5	—	0,25