


175 c.c. Bushman D14/4B

A motorcycle for any type of country. Originally built for the Australian market for use in the unkind conditions of the outback. The Bushman will take a lot of punishment and still give you safety, speed and economy. Competition tested front forks and trials tyres as standard. Finish is Bushfire Orange and White with forms and forks in Black.



175 c.c. D14/4S

The really sporty 175 c.c.! With four speed gear box, upswept exhaust pipe with heat guard, separate chromium headlamp, brand new sports front forks with rubber gaiters—in fact, all the extras that make it an eye-opener and a lot of motorcycle. Finished in Flamboyant Red and Chrome.



The best value in the motorcycle world, low in price, economical to run. The D14/4 offers over 100 m.p.g. from its new 13 horse power

engine. Light and easy to handle this model is offered in a choice of de-luxe colour finishes Black and Chrome, or Electric Blue and Chrome.



441 c.c. Shooting Star B44

The Shooting Star, the bigger brother of the Starfire, offers even more power, and riding comfort. The square finned power unit is almost identical to the famous Victor G. P. Specifications include built-up crankshaft assembly, forged steel flywheels, roller bearing big end and forged steel H-section connecting rod. Finish is Cherokee Red and Chrome.



250 c.c. Starfire B25

This is the fastest production 250 eve B.S.A. Built round a competition to with glass fibre petrol tank and side p incorporating a high performance engine developed from the famo Grand Prix. The overall feel of this ro of immediate response to your contrapletely reliable and very fast. Fit Sapphire Blue, Ivory and Chrome.







650 c.c. Lightning

A sports model with a pedigree feel and appeal. Speed equipped. Matched rubber mounted speedo and tachometer, twin leading shoe front brake and special two way front fork damping. All this and a lot more make this a machine in a million—the envy of other road users-very fast but easy to handle and ultra reliable under all conditions. Finished in Flamboyant Red, Chrome and polished alloy.



650 c.c. Firebird Scrambler

A winner time and again in the toughest American competitions, the Firebird is essentially a competition machine. Fitted with a brand new twin leading shoe front brake, provision for capacitor ignition, racing saddle and footrests front and rear. One of the fastest accelerating motorcycles ever tested. It's a real 'toughie'.



For full-powered fun

SPECIFICATION

MODEL	175 cc D14/4 D14/4S	175 cc Bushman D14/4B	250 cc B25 Starfire	441 cc B44SS Shooting Star	441 cc B44VS	
ENGINE Bore, mm. (ins.) Stroke, mm. (ins.) Capacity, cc. (cu. ins.) Compression ratio Valves Lubrication Ignition	61·5 (2·42) 58 (2·28) 173 (10·55) 10 : 1 None Petroil Coil	61·5 (2·42) 58 (2·28) 173 (10·55) 10 : 1 None Petroil E.T. coil	67 (2·64) 70 (2·75) 249 (15·19) 10 : 1 O.H.V. Dry sump Coil	79 (3·11) 90 (3·54) 441 (26·9) 9 : 4 : 1 O.H.V. Dry sump Coil	79 (3·11) 90 (3·54) 441 (26·9) 9 : 4 : 1 O.H.V. Dry sump Coil	
TRANSMISSION Sprockets: Engine Clutch Gearbox Rear wheel Top gear Third gear Second gear First gear Chain (front) Chain (rear)	17 38 16 47 6-58 8-55 12-04 18-68 38 × -250 ½ × -205	17 38 16 58 8-1 10-5 14-8 23-0 a/8 × ·250 1/2 × ·205	23 52 16 49 6·92 8·6 11·4 18·3 8 Duplex	28 52 17 47 5.14 6.42 8.97 13.6 3 Duplex 8 x ±	28 52 17 49 5-36 6-70 8-84 14-20 2 Duplex	
BRAKES Diam., front, ins. (cms.) Diam., rear, ins. (cms.)	5½ (13·97) 5½ (13·97)	5½ (13·97) 5½ (13·97)	7 (17·78) 7 (17·78)	8 (20·32) 7 (17·78)	8 (20·32) 7 (17·78)	
DUNLOP TYRES Size, front Size, rear	3·00 × 18 3·00 × 18	3·00 × 19 3·00 × 19	3·25 x 18 3·50 x 18	3·25 × 18 3·50 × 18	3·25 × 19 4·00 × 18	
Battery Headlamp dia., ins. (cms.) Voltage	10 a.h. 5" (12-7) 6	E.T. 5" (12·7) E.T.	10 a.h. 6½ (17) 12	10 a.h. 6½ (17) 12	10 a.h. 6½ (17) 12	
MISCELLANEOUS Fuel, galls. (litres) Oil, pints (litres). Seat height, ins. (cms.) Width, ins. (cms.) Length, ins. (cms.) Clearance, unladen Weight, lbs. (kilos)	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	2 (9) 30½ (77·5) 27¾ (73) 78 (198) 10 (25) 222 (100)	1 ³ / ₄ (8) 4 (2 ¹ / ₄) 31 (79) 28 (71) 82 (208) 7 ¹ / ₂ (19) 306 (139)	13/4 (8)/4 (2½) 31 (79) 28 (71) 82 (208) 7½ (19) 329 (149)	1 ² / ₄ (8) 5 (3) 32 (81·3) 32 (81·3) 82 (208) 8 ¹ / ₂ (21·4) 306 (139)	

MODEL	500 cc A50 Royal Star	650 cc A65-T Thunderbolt	650 cc A65-L Lightning	650 cc A65F-S Firebird Scrambler	650 cc A65-SS Spitfire Mk. IV
ENGINE Bore, mm. (ins.) Stroke, mm. (ins.) Capacity, cc. (cu. ins.) Compression ratio Valves Lubrication Ignition	65·5 (2·58)	75 (2-95)	75 (2·95)	75 (2.95)	75 (2·95)
	74 (2·91)	74 (2-91)	74 (2·91)	74 (2.91)	74 (2·91)
	499 (30·45)	654 (39-91)	654 (39·91)	654 (39.91)	654 (39·91)
	9 : 1	9 : 1	9 : 1	10 : 1	9 : 1
	O.H.V.	O.H.V.	O.H.V.	O.H.V.	O.H.V.
	Dry sump	Dry sump	Dry sump	Dry sump	Dry sump
	Twin coil	Twin coil	Twin coil	Twin coil	Twin coil
TRANSMISSION Sprockets: Engine Clutch Gearbox Rear wheel Top gear Third gear Second gear First gear Chain (front) Chain (rear)	28	28	28	28	28
	58	58	58	58	58
	18	20	20	20	20
	47	47	47	47	47
	5·41	4.87	4-87	4.87	4-87
	6·2	5.58	5-58	5.58	5-58
	8·67	7.8	7-8	7.8	7-8
	13·6	12.27	12-27	12.27	12-27
	3 Triple	a Triple	3 Triple	\$\frac{1}{2} \text{Triple}	\$ Triple
BRAKES Diam., front, ins. (cms.) Diam., rear, ins. (cms.)	8 (20·32)	8 (20·32)	8 (20·32) T.L.S.	8 (20·32) T.L.S.	8 (20·32) T.L.S.
	7 (17·78)	7 (17·78)	7 (17·78)	7 (17·78)	7 (17·78)
DUNLOP TYRES Size, front Size, rear	3·25 × 19 4·00 × 18	3·25 × 19 4·00 × 18	3·25 × 19 4·00 × 18	3·25 × 19 4·00 × 18	3·25 × 19 4·00 × 18
ELECTRICAL Battery Headlamp dia., ins. (cms.) Voltage	10 a.h. 6½ (17) 12	10 a.h. 6½ (17) 12	10 a.h. 6½ (17) 12	10 a.h. 5½ (14) 12	10 a.h. 6½ (17) 12
MISCELLANEOUS Fuel, galls. (litres) Oil, pints (litres) Seat height, ins. (cms.) Width, ins. (cms.) Length, ins. (cms.) Clearance, unladen Weight, lbs. (kilos)	2 ³ / ₄ (10)	4 (18)	4 (18)	1½ (8½)	5 (22½)
	5 (3)	5 (3)	5 (3)	5 (3)	5 (3)
	32 (81·3)	32 (81-3)	32 (81·3)	32 (81·3)	32 (81·3)
	28 (70)	28 (70)	28 (70)	28 (70)	28 (70)
	85 ¹ / ₄ (216)	85½ (216)	85½ (216)	85½ (216)	85¼ (216)
	8 (20·2)	8 (20-2)	8 (20·2)	7½ (19)	8 (20·2)
	408 (185)	404 (183)	412 (186)	411 (186)	408 (185)

Specifications are subject to alteration without notice and details of high performance equipment for certain models published separately.



650 c.c. Spitfire Mk. IV Special

The really big one—like it's airborn namesake, this machine has real punch! Things classed as extras on other motorcycles are standard on this one. Tuned engine with racing pistons. Racing style glass fibre petrol tank. Twin Amal concentric carburettors, light alloy rims and a brand new twin leading shoe front brake are but a portion of this motorcycle's host of special features. Cherokee Red, Chrome and polished alloy finish give the machine the looks to match its brilliant performance.



LUGNETS CYKELAFFÄR MOTOR & SPORT Torstensonsg. 34, Tel. 11 43 69 BORÁS

BSA MOTOR CYCLES LTD ARMOURY ROAD
Telephone VICTORIA 2381

BIRMINGHAM 11 ENGLAND
Telegrams: SELMOTO BIRMINGHAM

Ref. 3/68 EX Printed in England by W. P. Co. Ltd., Warwick